



## United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILI	NG DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/082,101	02/26/2002		Hajime Kimura	740756-2444	3503
31780	7590	12/16/2005		EXAMINER	
ERIC ROBI	NSON		PERUNGAVOOR, SATHYANARAYA V		
PMB 955 21010 SOUT	HBANK S	Т.		ART UNIT	PAPER NUMBER
POTOMAC I	FALLS, V	A 20165		2625	

DATE MAILED: 12/16/2005

Please find below and/or attached an Office communication concerning this application or proceeding.

	Application No.	Applicant(s)	
	10/082,101	KIMURA, HAJIME	
Office Action Summary	Examiner	Art Unit	
	Sath V. Perungavoor	2625	
The MAILING DATE of this communication app Period for Reply	ears on the cover sheet with the c	orrespondence address	
A SHORTENED STATUTORY PERIOD FOR REPLY WHICHEVER IS LONGER, FROM THE MAILING DA  - Extensions of time may be available under the provisions of 37 CFR 1.13 after SIX (6) MONTHS from the mailing date of this communication.  - If NO period for reply is specified above, the maximum statutory period w  - Failure to reply within the set or extended period for reply will, by statute, Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICATION 16(a). In no event, however, may a reply be tim rill apply and will expire SIX (6) MONTHS from cause the application to become ABANDONE	N. nely filed the mailing date of this communication. D (35 U.S.C. § 133).	
Status			
1)	action is non-final.  ace except for formal matters, pro		
Disposition of Claims			
4)  Claim(s) 11-26 is/are pending in the application 4a) Of the above claim(s) is/are withdraw 5)  Claim(s) is/are allowed. 6)  Claim(s) 11-26 is/are rejected. 7)  Claim(s) is/are objected to. 8)  Claim(s) are subject to restriction and/or	vn from consideration.		
Application Papers			
9) The specification is objected to by the Examiner 10) The drawing(s) filed on is/are: a) access Applicant may not request that any objection to the or Replacement drawing sheet(s) including the correction 11) The oath or declaration is objected to by the Examiner	epted or b) objected to by the Eddrawing(s) be held in abeyance. See ion is required if the drawing(s) is obj	e 37 CFR 1.85(a). jected to. See 37 CFR 1.121(d).	
Priority under 35 U.S.C. § 119			
12) Acknowledgment is made of a claim for foreign a) All b) Some * c) None of:  1. Certified copies of the priority documents 2. Certified copies of the priority documents 3. Copies of the certified copies of the prior application from the International Bureau * See the attached detailed Office action for a list of	s have been received. s have been received in Applicati ity documents have been receive (PCT Rule 17.2(a)).	on No ed in this National Stage	
Attachment(s)			
1) Notice of References Cited (PTO-892)	4) Interview Summary Paper No(s)/Mail Da		
<ul> <li>2) Notice of Draftsperson's Patent Drawing Review (PTO-948)</li> <li>3) Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)</li> <li>Paper No(s)/Mail Date</li> </ul>		Patent Application (PTO-152)	

# DETAILED ACTION

#### Continued Examination Under 37 CFR 1.114

[1] A request for continued examination under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on September 29, 2005 has been entered.

#### Response to Arguments

[2] Presented arguments have been fully considered, but are rendered moot in view of the new ground(s) of rejection.

#### Claim Objections

[3] Claim 20 is objected to because of the following informalities: there is no antecedent basis for a "first image signal". For examining purposes, the Examiner will assume the applicant intended to include a recitation similar to that of claim 19. Appropriate correction is required.

### Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

[4] Claims 11-14 are rejected under 35 U.S.C. 103(a) as being unpatentable over Spivey et al. ("Spivey") [US 5,886,353] in view of Sakai et al. ("Sakai") [US 5,420,703].

Regarding claim 11, Spivey discloses the following claim limitations:

A device comprising [Figure 1]: a pixel portion having a plurality of pixels each comprising a photoelectric conversion element [Column 4 Lines 5-10: electronic signals ... photons absorbed]; and means for determining a defective pixel [Column 15 Lines 14-16], wherein the defective pixel is determined by the steps of: obtaining a first image signal of each of the plurality of pixels by using the photoelectric conversion element [Column 15 Lines 23-25: white field images]; obtaining a second image signal of each of the plurality of pixels by using the photoelectric conversion element [Column 15 Lines 23-25: dark field images]; calculating a first difference between the first and second image signals of each of the plurality of pixels [Column 15 Lines 27-30: subtracted]; obtaining at least a value selected from a modal value, an average value and a maximum value of the first difference of each of the plurality of pixels [Column 15] Lines 27-30: averaged; and determining whether each of the plurality of pixels is the defective pixel by obtaining a second difference between the first difference of each of the plurality of pixels and the value selected from a modal value, an average value and a maximum value of the first difference of the plurality of pixels [Column 15 Lines *30-34: variation*].

Spivey does not explicitly disclose the following claim limitations:

Reading a first calibration sheet to obtain a first image signal.

Reading a second calibration sheet to obtain a second image signal.

Art Unit: 2625

Page 4

However, in the same field of endeavor Sakai discloses the deficient claim limitations, as follows:

Reading a first calibration sheet to obtain a first image signal [Column 4 Lines 17-18: white board]. Reading a second calibration sheet to obtain a second image signal [Column 4 Lines 17-18: black board].

Spivey and Sakai are combinable because they are from the same field of sensor calibration. It would have been obvious to one with ordinary skill in the art at the time of invention to modify the teachings of Spivey with Sakai to read white and black sheets to obtain white and black image signals, the motivation being to correct sensor sensitivity variations by amount of light that is reflected [Column 4 Lines 58-63].

Regarding claim 12, Spivey discloses the following claim limitations:

A device comprising [Figure 1]: a pixel portion having a plurality of pixels each comprising a photoelectric conversion element [Column 4 Lines 5-10: electronic signals ... photons absorbed]; and means for determining a defective pixel [Column 15 Lines 14-16], wherein the defective pixel is determined by the steps of: obtaining a first image signal of each of the plurality of pixels by using the photoelectric conversion element [Column 15 Lines 23-25: white field images]; obtaining a second image signal of each of the plurality of pixels by using the photoelectric conversion element [Column 15 Lines 23-25: dark field images]; calculating a first difference between the first and second image signals of each of the plurality of pixels [Column 15 Lines 27-30: subtracted]; obtaining at least a value selected from a modal value, an average value and a maximum value of the first difference of each of the plurality of pixels [Column 15

Lines 27-30: averaged]; and determining whether each of the plurality of pixels is the defective pixel by obtaining a second difference between the first difference of each of the plurality of pixels and the value selected from a modal value, an average value and a maximum value of the first difference of the plurality of pixels [Column 15 Lines 30-34: variation].

Spivey does not explicitly disclose the following claim limitations:

Reading a first calibration sheet to obtain a first image signal.

Reading a second calibration sheet to obtain a second image signal.

However, in the same field of endeavor Sakai discloses the deficient claim limitations, as follows:

Reading a first calibration sheet to obtain a first image signal [Column 4 Lines 17-18: white board]. Reading a second calibration sheet to obtain a second image signal [Column 4 Lines 17-18: black board].

Spivey and Sakai are combinable because they are from the same field of sensor calibration. It would have been obvious to one with ordinary skill in the art at the time of invention to modify the teachings of Spivey with Sakai to read white and black sheets to obtain white and black image signals, the motivation being to correct sensor sensitivity variations by amount of light that is reflected [Column 4 Lines 58-63].

Neither Spivey nor Sakai explicitly disclose the following:

Calculating the first ratio and the second ratio.

At the time of the invention, it would have been obvious to a person of ordinary skill in the art to substitute the subtraction operation with a ratio operation. Applicant has not disclosed that ratios provide for superior results over subtraction, is used for a particular purpose or

Art Unit: 2625

Page 6

Applicant's invention to perform equally well with subtraction because it the variation (i.e. variance) that ultimately determines whether a pixel is defective or not, it makes no difference how the variance is obtained. Hence, a variance obtained from via subtraction has the same effect as the variance obtained from via ratios. Therefore, it would have been obvious to one of ordinary skill in this art to modify Spivey to use ratios instead of subtraction to obtain the invention as specified in claim 12.

Regarding claim 13, Sakai meets all the claim limitations, as follows:

A device according to claim 11, wherein the device is at least a device selected from the group of a hand scanner, a video camera, a digital still camera, a notebook computer, a mobile computer, a cellular phone, a portable game machine and an electronic book [1] on Figure 1].

Regarding claim 14, Sakai meets all the claim limitations, as follows:

A device according to claim 12, wherein the device is at least a device selected from the group of a hand scanner, a video camera, a digital still camera, a notebook computer, a mobile computer, a cellular phone, a portable game machine and an electronic book [1 on Figure 1].

[5] Claims 15-18 and 21-24 are rejected under 35 U.S.C. 103(a) as being unpatentable over Spivey et al. ("Spivey") [US 5,886,353] in view of Sakai et al. ("Sakai") [US 5,420,703] further in view of Levine [US 4,562,473].

Regarding claim 15, Spivey discloses the following claim limitations:

A device comprising [Figure 1]: a pixel portion having a plurality of pixels each comprising a photoelectric conversion element [Column 4 Lines 5-10: electronic signals ... photons absorbed]; and means for determining a defective pixel [Column 15 Lines 14-16], wherein the defective pixel is determined by the steps of: obtaining a first image signal of each of the plurality of pixels by using the photoelectric conversion element [Column 15 Lines 23-25: white field images]; obtaining a second image signal of each of the plurality of pixels by using the photoelectric conversion element [Column 15 Lines 23-25: dark field images]; calculating a first difference between the first and second image signals of each of the plurality of pixels [Column 15 Lines 27-30: subtracted]; obtaining at least a value selected from a modal value, an average value and a maximum value of the first difference of each of the plurality of pixels [Column 15] Lines 27-30: averaged; and determining whether each of the plurality of pixels is the defective pixel by obtaining a second difference between the first difference of each of the plurality of pixels and the value selected from a modal value, an average value and a maximum value of the first difference of the plurality of pixels [Column 15 Lines 30-34: variation].

Spivey does not explicitly disclose the following claim limitations:

Reading a second calibration sheet to obtain a second image signal.

However, in the same field of endeavor Sakai discloses the deficient claim limitations, as follows:

Reading a second calibration sheet to obtain a second image signal [Column 4 Lines 17-18: black board].

Spivey and Sakai are combinable because they are from the same field of sensor calibration. It would have been obvious to one with ordinary skill in the art at the time of invention to modify the teachings of Spivey with Sakai to read a black sheet to obtain a black image signal, the motivation being to correct sensor sensitivity variations by amount of light that is reflected [Column 4 Lines 58-63].

Neither Spivey nor Sakai explicitly disclose the following:

The first image signal of each of the plurality of pixels is obtained while T>{C x Vp/Id} is satisfied, where T is an accumulation time, C is a capacitance of the photoelectric conversion element, Vp is a voltage applied to the photoelectric conversion element.

However, in the same field of endeavor Levine discloses the deficient claim limitations, as follows:

Longer accumulation time shifts the black level toward a white level, due to dark current [Column 1 Lines 22-26].

Spivey, Sakai and Levine are combinable because they are from the same field of sensor calibration.

It would have been obvious to one with ordinary skill in the art at the time of invention to modify the teachings of Spivey and Sakai with Levine to obtain a first image signal of each of the plurality of pixels when T>{C x Vp/Id}. First, it is well established that T>{C x Vp/Id}

is the time required to completely discharge the capacitive element in the photodiode [See, Tsuruta et al. ("Tsuruta") [US 5,233,180] at Column 10 Equation 19]. Second, longer accumulation time leads to dark current based capacitive discharging, leading to conversion from a black level to a white level. Hence, one of ordinary skill would understand that complete discharging of photodiode (i.e. T>{C x Vp/Id}) would result in a white image signal. Therefore, one of ordinary skill would upon reading Levine's disclosure understand that Spivey's white image signal can be obtained through complete discharge of the photodiode. The motivation to combine Spivey, Sakai and Levine being the elimination of a white calibration sheet.

Regarding claim 16, Spivey discloses the following claim limitations:

A device comprising [Figure 1]: a pixel portion having a plurality of pixels each comprising a photoelectric conversion element [Column 4 Lines 5-10: electronic signals ... photons absorbed]; and means for determining a defective pixel [Column 15 Lines 14-16], wherein the defective pixel is determined by the steps of: obtaining a first image signal of each of the plurality of pixels by using the photoelectric conversion element [Column 15 Lines 23-25: white field images]; obtaining a second image signal of each of the plurality of pixels by using the photoelectric conversion element [Column 15 Lines 23-25: dark field images]; calculating a first difference between the first and second image signals of each of the plurality of pixels [Column 15 Lines 27-30: subtracted]; obtaining at least a value selected from a modal value, an average value and a maximum value of the first difference of each of the plurality of pixels [Column 15 Lines 27-30: averaged]; and determining whether each of the plurality of pixels is the

Art Unit: 2625

Page 10

defective pixel by obtaining a second difference between the first difference of each of the plurality of pixels and the value selected from a modal value, an average value and a maximum value of the first difference of the plurality of pixels [Column 15 Lines 30-34: variation].

Spivey does not explicitly disclose the following claim limitations:

Reading a second calibration sheet to obtain a second image signal.

However, in the same field of endeavor Sakai discloses the deficient claim limitations, as follows:

Reading a second calibration sheet to obtain a second image signal [Column 4 Lines 17-18: black board].

Spivey and Sakai are combinable because they are from the same field of sensor calibration. It would have been obvious to one with ordinary skill in the art at the time of invention to modify the teachings of Spivey with Sakai to read a black sheet to obtain a black image signal, the motivation being to correct sensor sensitivity variations by amount of light that is reflected [Column 4 Lines 58-63].

Neither Spivey nor Sakai explicitly disclose the following:

The first image signal of each of the plurality of pixels is obtained while T>{C x Vp/Id} is satisfied, where T is an accumulation time, C is a capacitance of the photoelectric conversion element, Vp is a voltage applied to the photoelectric conversion element.

However, in the same field of endeavor Levine discloses the deficient claim limitations, as follows:

Art Unit: 2625

Longer accumulation time shifts the black level toward a white level, due to dark current [Column 1 Lines 22-26].

Spivey, Sakai and Levine are combinable because they are from the same field of sensor calibration.

It would have been obvious to one with ordinary skill in the art at the time of invention to modify the teachings of Spivey and Sakai with Levine to obtain a first image signal of each of the plurality of pixels when T> {C x Vp/Id}. First, it is well established that T> {C x Vp/Id} is the time required to completely discharge the capacitive element in the photodiode [See, Tsuruta et al. ("Tsuruta") [US 5,233,180] at Column 10 Equation 19]. Second, longer accumulation time leads to dark current based capacitive discharging, leading to conversion from a black level to a white level. Hence, one of ordinary skill would understand that complete discharging of photodiode (i.e. T> {C x Vp/Id}) would result in a white image signal. Therefore, one of ordinary skill would upon reading Levine's disclosure understand that Spivey's white image signal can be obtained through complete discharge of the photodiode. The motivation to combine Spivey, Sakai and Levine being the elimination of a white calibration sheet.

Spivey, Sakai and Levine does not explicitly disclose expressly the following:

Calculating the first ratio and the second ratio.

At the time of the invention, it would have been obvious to a person of ordinary skill in the art to substitute the subtraction operation with a ratio operation. Applicant has not disclosed that ratios provide for superior results over subtraction, is used for a particular purpose or solves a stated problem. One of ordinary skill in the art, furthermore, would have expected Applicant's invention to perform equally well with subtraction because it the variation (i.e.

variance) that ultimately determines whether a pixel is defective or not, it makes no difference how the variance is obtained. Hence, a variance obtained from via subtraction has the same effect as the variance obtained from via ratios. Therefore, it would have been obvious to one of ordinary skill in this art to modify Spivey to use ratios instead of subtraction to obtain the invention as specified in claim 16.

Regarding claim 17, Spivey discloses the following claim limitations:

A device comprising [Figure 1]: a pixel portion having a plurality of pixels each comprising a photoelectric conversion element [Column 4 Lines 5-10: electronic signals ... photons absorbed]; and means for determining a defective pixel [Column 15 Lines 14-16], wherein the defective pixel is determined by the steps of: obtaining a first image signal of each of the plurality of pixels by using the photoelectric conversion element [Column 15 Lines 23-25: dark field images]; obtaining a second image signal of each of the plurality of pixels by using the photoelectric conversion element [Column 15 Lines 23-25: white field images]; calculating a first difference between the first and second image signals of each of the plurality of pixels [Column 15 Lines 27-30: subtracted]; obtaining at least a value selected from a modal value, an average value and a maximum value of the first difference of each of the plurality of pixels /Column 15 Lines 27-30: averaged; and determining whether each of the plurality of pixels is the defective pixel by obtaining a second difference between the first difference of each of the plurality of pixels and the value selected from a modal value, an average value and a maximum value of the first difference of the plurality of pixels [Column 15 Lines *30-34: variation*].

Spivey does not explicitly disclose the following claim limitations:

Reading a second calibration sheet to obtain a second image signal.

However, in the same field of endeavor Sakai discloses the deficient claim limitations, as follows:

Reading a second calibration sheet to obtain a second image signal [Column 4 Lines 17-18: white board].

Spivey and Sakai are combinable because they are from the same field of sensor calibration. It would have been obvious to one with ordinary skill in the art at the time of invention to modify the teachings of Spivey with Sakai to read a white sheet to obtain a white image signal, the motivation being to correct sensor sensitivity variations by amount of light that is reflected [Column 4 Lines 58-63].

Neither Spivey nor Sakai explicitly disclose the following:

The first image signal of each of the plurality of pixels is obtained while an accumulation time of the photoelectric conversion element is 0

However, in the same field of endeavor Levine discloses the deficient claim limitations, as follows:

Longer accumulation time shifts the black level toward a white level, due to dark current [Column 1 Lines 22-26].

Spivey, Sakai and Levine are combinable because they are from the same field of sensor calibration.

It would have been obvious to one with ordinary skill in the art at the time of invention to modify the teachings of Spivey and Sakai with Levine to obtain a first image signal while the accumulation time is 0. In order to obtain a true black level the time needs to be 0, else the

effects of dark current would cause the black level to fade. The motivation to combine Spivey, Sakai and Levine being the elimination of a black calibration sheet.

Regarding claim 18, Spivey discloses the following claim limitations:

A device comprising /Figure 1]: a pixel portion having a plurality of pixels each comprising a photoelectric conversion element [Column 4 Lines 5-10: electronic signals ... photons absorbed]; and means for determining a defective pixel [Column 15 Lines 14-16], wherein the defective pixel is determined by the steps of: obtaining a first image signal of each of the plurality of pixels by using the photoelectric conversion element [Column 15 Lines 23-25: dark field images]; obtaining a second image signal of each of the plurality of pixels by using the photoelectric conversion element [Column 15 Lines 23-25: white field images]; calculating a first difference between the first and second image signals of each of the plurality of pixels [Column 15 Lines 27-30: subtracted]; obtaining at least a value selected from a modal value, an average value and a maximum value of the first difference of each of the plurality of pixels [Column 15] Lines 27-30: averaged; and determining whether each of the plurality of pixels is the defective pixel by obtaining a second difference between the first difference of each of the plurality of pixels and the value selected from a modal value, an average value and a maximum value of the first difference of the plurality of pixels [Column 15 Lines *30-34: variation*].

Spivey does not explicitly disclose the following claim limitations:

Reading a second calibration sheet to obtain a second image signal.

However, in the same field of endeavor Sakai discloses the deficient claim limitations, as follows:

Reading a second calibration sheet to obtain a second image signal [Column 4 Lines 17-18: white board].

Spivey and Sakai are combinable because they are from the same field of sensor calibration. It would have been obvious to one with ordinary skill in the art at the time of invention to modify the teachings of Spivey with Sakai to read a white sheet to obtain a white image signal, the motivation being to correct sensor sensitivity variations by amount of light that is reflected [Column 4 Lines 58-63].

Neither Spivey nor Sakai explicitly disclose the following:

The first image signal of each of the plurality of pixels is obtained while an accumulation time of the photoelectric conversion element is 0

However, in the same field of endeavor Levine discloses the deficient claim limitations, as follows:

Longer accumulation time shifts the black level toward a white level, due to dark current [Column 1 Lines 22-26].

Spivey, Sakai and Levine are combinable because they are from the same field of sensor calibration.

It would have been obvious to one with ordinary skill in the art at the time of invention to modify the teachings of Spivey and Sakai with Levine to obtain a first image signal while the accumulation time is 0. In order to obtain a true black level the time needs to be 0, else the effects of dark current would cause the black level to fade. The motivation to combine Spivey, Sakai and Levine being the elimination of a black calibration sheet.

Spivey, Sakai and Levine does not explicitly disclose expressly the following:

Calculating the first ratio and the second ratio.

At the time of the invention, it would have been obvious to a person of ordinary skill in the art to substitute the subtraction operation with a ratio operation. Applicant has not disclosed that ratios provide for superior results over subtraction, is used for a particular purpose or solves a stated problem. One of ordinary skill in the art, furthermore, would have expected Applicant's invention to perform equally well with subtraction because it the variation (i.e. variance) that ultimately determines whether a pixel is defective or not, it makes no difference how the variance is obtained. Hence, a variance obtained from via subtraction has the same effect as the variance obtained from via ratios. Therefore, it would have been obvious to one of ordinary skill in this art to modify Spivey to use ratios instead of subtraction to obtain the invention as specified in claim 18.

Regarding claim 21, Sakai meets all the claim limitations, as follows:

A device according to claim 15, wherein the device is at least a device selected from the group of a hand scanner, a video camera, a digital still camera, a notebook computer, a mobile computer, a cellular phone, a portable game machine and an electronic book [1 on Figure 1].

Regarding claim 22-24, all claimed limitations are set forth and rejected as per discussion for claim 21.

[6] Claims 19, 20, 25 and 26 are rejected under 35 U.S.C. 103(a) as being unpatentable over Spivey et al. ("Spivey") [US 5,886,353] in view of Levine [US 4,562,473].

Regarding claim 19, Spivey discloses the following claim limitations:

A device comprising [Figure 1]: a pixel portion having a plurality of pixels each comprising a photoelectric conversion element [Column 4 Lines 5-10: electronic signals ... photons absorbed]; and means for determining a defective pixel [Column 15 Lines 14-16], wherein the defective pixel is determined by the steps of: obtaining a first image signal of each of the plurality of pixels by using the photoelectric conversion element [Column 15 Lines 23-25: white field images]; obtaining a second image signal of each of the plurality of pixels by using the photoelectric conversion element [Column 15 Lines 23-25: dark field images]; calculating a first difference between the first and second image signals of each of the plurality of pixels [Column 15 Lines 27-30: subtracted]; obtaining at least a value selected from a modal value, an average value and a maximum value of the first difference of each of the plurality of pixels [Column 15] Lines 27-30: averaged]; and determining whether each of the plurality of pixels is the defective pixel by obtaining a second difference between the first difference of each of the plurality of pixels and the value selected from a modal value, an average value and a maximum value of the first difference of the plurality of pixels [Column 15 Lines 30-34: variation].

Spivey does not explicitly disclose the following:

The first image signal of each of the plurality of pixels is obtained while T>{C x Vp/Id} is satisfied, where T is an accumulation time, C is a capacitance of the photoelectric conversion element, Vp is a voltage applied to the photoelectric

Art Unit: 2625

conversion element, and wherein the second image signal of each of the plurality of pixels is obtained while an accumulation time of the photoelectric conversion element is 0.

However, in the same field of endeavor Levine discloses the deficient claim limitations, as follows:

Longer accumulation time shifts the black level toward a white level, due to dark current [Column 1 Lines 22-26].

Spivey and Levine are combinable because they are from the same field of sensor calibration. It would have been obvious to one with ordinary skill in the art at the time of invention to modify the teachings of Spivey and Sakai with Levine to obtain a first image signal of each of the plurality of pixels when T>{C x Vp/Id}. First, it is well established that T>{C x Vp/Id} is the time required to completely discharge the capacitive element in the photodiode [See, Tsuruta et al. ("Tsuruta") [US 5,233,180] at Column 10 Equation 19]. Second, longer accumulation time leads to dark current based capacitive discharging, leading to conversion from a black level to a white level. Hence, one of ordinary skill would understand that complete discharging of photodiode (i.e. T>{C x Vp/Id}) would result in a white image signal. Therefore, one of ordinary skill would upon reading Levine's disclosure understand that Spivey's white image signal can be obtained through complete discharge of the photodiode. It would have been also obvious to one with ordinary skill in the art at the time of invention to modify the teachings of Spivey and Sakai with Levine to obtain a second image signal while the accumulation time is 0. In order to obtain a true black level the time needs to be 0, else the effects of dark current would cause the black level to fade. The

motivation to combine Spivey and Levine being an alternative method for generating white and black image signals.

Regarding claim 20, Spivey discloses the following claim limitations:

A device comprising [Figure 1]: a pixel portion having a plurality of pixels each comprising a photoelectric conversion element [Column 4 Lines 5-10: electronic signals ... photons absorbed]; and means for determining a defective pixel [Column 15 Lines 14-16], wherein the defective pixel is determined by the steps of: obtaining a first image signal of each of the plurality of pixels by using the photoelectric conversion element [Column 15 Lines 23-25: white field images]; obtaining a second image signal of each of the plurality of pixels by using the photoelectric conversion element [Column 15 Lines 23-25: dark field images]; calculating a first difference between the first and second image signals of each of the plurality of pixels [Column 15 Lines 27-30: subtracted]; obtaining at least a value selected from a modal value, an average value and a maximum value of the first difference of each of the plurality of pixels /Column 15 Lines 27-30: averaged; and determining whether each of the plurality of pixels is the defective pixel by obtaining a second difference between the first difference of each of the plurality of pixels and the value selected from a modal value, an average value and a maximum value of the first difference of the plurality of pixels [Column 15 Lines 30-34: variation].

Spivey does not explicitly disclose the following:

The first image signal of each of the plurality of pixels is obtained while T>{C x Vp/Id} is satisfied, where T is an accumulation time, C is a capacitance of the

photoelectric conversion element, Vp is a voltage applied to the photoelectric conversion element, and wherein the second image signal of each of the plurality of pixels is obtained while an accumulation time of the photoelectric conversion element is 0.

However, in the same field of endeavor Levine discloses the deficient claim limitations, as follows:

Longer accumulation time shifts the black level toward a white level, due to dark current [Column 1 Lines 22-26].

Spivey and Levine are combinable because they are from the same field of sensor calibration. It would have been obvious to one with ordinary skill in the art at the time of invention to modify the teachings of Spivey and Sakai with Levine to obtain a first image signal of each of the plurality of pixels when T>{C x Vp/Id}. First, it is well established that T>{C x Vp/Id} is the time required to completely discharge the capacitive element in the photodiode [See, Tsuruta et al. ("Tsuruta") [US 5,233,180] at Column 10 Equation 19]. Second, longer accumulation time leads to dark current based capacitive discharging, leading to conversion from a black level to a white level. Hence, one of ordinary skill would understand that complete discharging of photodiode (i.e. T>{C x Vp/Id}) would result in a white image signal. Therefore, one of ordinary skill would upon reading Levine's disclosure understand that Spivey's white image signal can be obtained through complete discharge of the photodiode. It would have been also obvious to one with ordinary skill in the art at the time of invention to modify the teachings of Spivey and Sakai with Levine to obtain a second image signal while the accumulation time is 0. In order to obtain a true black level to fade. The

Art Unit: 2625

Page 21

motivation to combine Spivey and Levine being an alternative method for generating white and black image signals.

Spivey and Levine does not explicitly disclose expressly the following:

Calculating the first ratio and the second ratio.

At the time of the invention, it would have been obvious to a person of ordinary skill in the art to substitute the subtraction operation with a ratio operation. Applicant has not disclosed that ratios provide for superior results over subtraction, is used for a particular purpose or solves a stated problem. One of ordinary skill in the art, furthermore, would have expected Applicant's invention to perform equally well with subtraction because it the variation (i.e. variance) that ultimately determines whether a pixel is defective or not, it makes no difference how the variance is obtained. Hence, a variance obtained from via subtraction has the same effect as the variance obtained from via ratios. Therefore, it would have been obvious to one of ordinary skill in this art to modify Spivey to use ratios instead of subtraction to obtain the invention as specified in claim 20.

Regarding claim 25, Levine meets all the claim limitations, as follows:

A device according to claim 19, wherein the device is at least a device selected from the group of a hand scanner, a video camera, a digital still camera, a notebook computer, a mobile computer, a cellular phone, a portable game machine and an electronic book [Column 5 Line 19].

Regarding claim 26, Levine meets all the claim limitations, as follows:

Art Unit: 2625

A device according to claim 20, wherein the device is at least a device selected from

Page 22

the group of a hand scanner, a video camera, a digital still camera, a notebook

computer, a mobile computer, a cellular phone, a portable game machine and an

electronic book [Column 5 Line 19].

**Contact Information** 

[7] Any inquiry concerning this communication or earlier communications from the examiner

should be directed to Mr. Sath V. Perungavoor whose telephone number is (571) 272-7455. The

examiner can normally be reached on Monday to Friday from 8:30am to 5:00pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor,

Mr. Bhavesh M. Mehta whose telephone number is (571) 272-7453, can be reached on Monday to

Friday from 9:00am to 5:00pm. The fax phone number for the organization where this application

or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent

Application Information Retrieval (PAIR) system. Status information for published applications

may be obtained from either Private PAIR or Public PAIR. Status information for unpublished

applications is available through Private PAIR only. For more information about the PAIR system,

see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system,

contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Dated: December 1, 2005

Group Art Unit: 2625

Telephone: (571) 272-7455